

KEY TECHNOLOGY



Proprietary
Foam Nose Seal



3 Panel Construction



Fluid Resistant Level 3 160 mmHg



Low Breathing Resistance Filter

FEATURES

- Advanced multilayer technology providing protection against mechanically and thermally generated particulates including: fluids, dusts, mists, fumes and smoke
- Three panel design provides structural integrity, form fit seal and optimal comfort. All three mask panels and seams have been independently tested and certified to AS 4381:2015 Level 3 – ISO 22609
- Bacterial Filtration Efficiency (BFE) >99%
- Fluid resistance level 3, 160 mmHg
- Proprietary adjustable foam nose pad to ensure consistent optimum facial seal and reduce fogging of eyewear
- Versatile unisex fit suitable for a vast range of facial shapes and sizes. Effective for many "hard to fit" individuals
- Specialised TRIDENT® respirator seal attains unrivalled PortaCount® fit testing results
- Low breathing resistance maximising wearer comfort, durability and life of product
- Designed to be used in conjunction with other mandatory personal protective equipment
- Latex free
- Each mask is individually batch numbered and packaged for the ultimate in traceability, portability and hygiene

AREAS OF APPLICATION

- Particulate Filtration
- Bacterial & Fluid Protection
- Personal Hygiene & Safety

STORAGE





STANDARDS & CERTIFICATIONS



CERTIFIED P2 AS/NZS 1716: 2012 ID No. BMP 732382

AS 4381: 2015 Level 3 ID No. BMP 737354 EN 149:2001 + A1:2009 ID No. BMP 754423





P2 LEVEL 3 SURGICAL RESPIRATOR











SIZING

Extra Small	RTCFFP2XS	
Small	RTCFFP2S	
Regular	RTCFFP2	
Regular Extended Length Head Straps	RTCFFP2E	
XX Large	RTCFFP2XXL	

PACKAGING

1 mask per bag 20 masks per inner 480 masks per carton

RTCFFP2XS	400 x 2/0 x 620mm GW: 6kg NW: 3,4kg
RTCFFP2S	440 x 300 x 620mm GW: 7.4kg NW: 4.5kg
RTCFFP2	630 x 250 x 580mm GW: 8kg NW: 4.5kg
RTCFFP2E	630 x 250 x 620mm GW: 8.1kg NW: 4.5kg
RTCFFP2XXL	680 x 260 x 610mm



