

RICOCHET TL-1 TEMPORARY BARRIERS



Jaybro

CONSIDER IT DONE.



- ✓ **Superior Design**
- ✓ **Superior Safety**
- ✓ **Superior Performance**

RICOCHET 

www.jaybro.com.au
sales@jaybro.com.au

Call Today!
1300 885 364

SAFETY FOR YOU AND EVERYONE ELSE.

The **Ricochet Safety Barrier** is designed to have the greatest energy absorbing capability. This provides a greater degree of safety and a lower risk of injury with any vehicle impact.

The TL-1 water filled barriers are tested to AASHTO MASH-1 standard and are rated for TL-1 (50km/hr). The dimensions are 2000 x 1000 x 580mm (L x H x W) and have a pin to pin length of 1.7m when interconnected. Each barrier has an empty weight of 62kg and a filled weight of 660kg.

The required end treatments consist of two barriers and one cap providing a flat end surface allowing safety delineation to be attached to the end treatment. The end treatments must not be water filled.

Each barrier has a drain point on each side allowing water to be drained safely without entering live traffic lanes and the fill point is designed so water can be sucked out if required. Each barrier also has two 22mm mounting holes in the top that allow screens to be installed, removing the distraction of work zone activity for drivers.

When installing the Ricochet barrier system all care and attention must be taken in accordance with the Ricochet Product and Installation manual. This manual is available on request.

Deflection:

TL 1 – 2.28m (50 km/h, 2770 kg pick-up, 25° angle)

